

# PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE : (62-21) 571 2998 FAX : (62-21) 571 2678 
 No.
 : EBCI/MSDS/2096

 Issue date
 :March,21, 2001

 Rev. no.
 : 03

 Rev. date
 : Octber, 01 2009

 Page no.
 : 1 of 3

# MATERIAL SAFETY DATA SHEET

## **I. PRODUCT IDENTIFICATION**

<ul> <li>Product name : EBP 2202 HV</li> <li>Common chemical name : Unsaturated polyester Resin</li> <li>Synonyms : High reactivity and promoted of ortho type unsaturated polyester resin</li> <li>II. INFORMATION ON INGREDIENT</li> </ul>								
Hazardous Ingredients	: %	CAS Number	EC number					
Styrene Monomer	: 10 - 40	100-42-5	202-851-5					
III. HAZARD IDENTIFICATION								
Potential Health Effect:								
Eye contact:	: Irritation, tear	Irritation, tearing, eye damage						
Skin contact	: Irritation, sym	Irritation, symptoms of drunkenness						
Ingestion	0	Irregular heartbeat, kidney damage, liver damage, cancer						
📕 Inhalation		Irritation, metallic taste, vomiting, headache, symptoms of drunkenness, liver damage, coma						
	damage, oon							
IV. FIRST AID MEASURES								
Eve contact	: Rinse with pl	Rinse with plenty of water immediately. Seek medical attention.						
Skin contact		Wash with plenty of soap and a large amount of water immediately. Take the						
•		contaminated clothing off. Seek medical attention if irritation develops. Do not induce vomiting because of risk of aspiration. Rinse mouth with water.						
	Seek medica	Seek medical attention.						
Inhalation		Move to fresh air and take a rest. Apply artificial respiration if difficulty in breathing. Seek medical attention after significant exposure.						
	broatining. Oc		ter significant expectate.					
V. FIRE FIGHTING MEASURES								
Flash Point	: 31.1 °C (tag	closed cup).						
Boiling point	: 145,0° C (76							
Ignition temperature	: 490,0° C							
Fire fighting		pray to cool fire exposi emical, or water spray to	ure surfaces and to protect o extinguish fire.	personnel. Use				
Hazardous product of combustion	: Carbon mono	oxide (CO).	-					
unusual fire & explosion hazard	: None known							
Lower explosion limit	: 1,1 %							
Upper explosion limit	: 8,0 %	8,0 %						
Protection of fire fighters	: Wear protect	ive clothing & use self-	contained breathing apparat	us.				



# PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE : (62-21) 571 2998 FAX : (62-21) 571 2678 
 No.
 : EBCI/MSDS/2096

 Issue date
 :March,21, 2001

 Rev. no.
 : 03

 Rev. date
 : Octber, 01 2009

 Page no.
 : 2 of 3

# **VI. ACCIDENTAL RELEASE MEASURES**

- Personal precaution
   Environmental precaution
   Keep away from drains, ground water & soil.
   Collect as much as possible in a container for disposal. Cover the remainder with inert absorbent, sand or soil. Disposal according to local regulations.

  VII. STORAGE AND HANDLING
  - Handling : Keep away from heat, sources of ignition, and no smoking. Storage : Keep in a cool, dry and well-ventilated place.

This product is stable under normal conditions of handling and storage.

## **VIII. PERSONAL PROTECTION**

Personal Protective Equipment	
📕 Eyes	: Use safety glasses with side shield.
Hands	: Although this material doesn't irritate skin significantly. To minimize skin contamination by following good industrial practice. Wearing protective gloves is recommended.
🖶 Skin & body	<ul> <li>Although this material doesn't irritate skin significantly. To minimize skin contamination by following good industrial practice. Wash contaminated skin thoroughly after handling. Avoid breathing vapour.</li> </ul>
Respiratory system	<ul> <li>Use local exhaust ventilation or handle in a ventilated enclosure. For greater protection wear respiratory protective equipment is recommended.</li> </ul>

## IX. PHYSICAL PROPERTIES

<ul> <li>Physical state &amp; appearance</li> <li>Viscosity at 25° C,Brookfield#3/60</li> <li>Odor</li> <li>Boiling point</li> </ul>	: : :	Red violet 700 - 800 cPs Styrene like 160 – 260°C
<ul> <li>Boiling point</li> <li>Water solubility</li> <li>Specific Gravity (25°C)</li> </ul>	:	160 – 260°C Insoluble 1.1 – 1.12 g/ml

# X. STABILITY & REACTIVITY

	Stability, in darkness at $25^{\circ}$ C	:	3 – 6 months
	Condition to avoid	:	Excessive heating.
	Material to avoid	:	None known
4	Hazardous Decomposition Product	:	None known



#### PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE : (62-21) 571 2998 FAX : (62-21) 571 2678 
 No.
 : EBCI/MSDS/2096

 Issue date
 :March,21, 2001

 Rev. no.
 : 03

 Rev. date
 : Octber, 01 2009

 Page no.
 : 3 of 3

# XI. TOXICOLOGICAL INFORMATION

PT. Eternal Buana Chemical Industries has not conducted toxicity studies on this material. No toxicological information is available

### **XII. COMPONENT INFORMATION**

Polycondensation product of carbodicylic acids or anhydrides with dihydroxy alcohols. The polymer is cotaining unsaturation and dissolved in styrene monomer as crosslinking agent.

## XIII. ECOLOGICAL INFORMATION

PT. Eternal Buana Chemical Industries has not conducted environmental toxicity or biodegradation studies on this material. No ecological information of this material is available.

## XIV. DISPOSAL CONSIDERATION

Disposal method

Controlled incineration or recycle.

#### **XV. TRANSPORT INFORMATION**

International transportation regulations :

🗕 UN number

Proper shipping name

Clasification of Hazardous Materials

Resin in solution (flammable liquids)



## **XVI. REGULATORY INFORMATION**

Local regulations

Not available

1866

3.3

:

## **XVII. OTHER INFORMATION**

This above data and information applies to the product as such and confirming to specifications given PT. Eternal Buana Chemical Industries. While the information is believed to be correct, PT. Eternal Buana Chemical Industries shall in no event be responsible for any damages what so ever, directly or indirectly resulting from the publication or use of or reliance upon data contained here in. Users are advised of possible additional hazard when the product is used in applications for which it was not intended. This sheet only be used and reproduced for prevention and security purposes.