



TECHNICAL DATA SHEET

ACRYNAL 7101 - 50 LV

I. DESCRIPTION

ACRYNAL 7101 - 50 LV is an acrylic copolymer solution designed mainly for lacquers, walls and concrete.

II. PERFORMANCE

- Good adhesion and hardness.
- Good gloss.
- Weathering resistance.

III. SUGGESTED USES

- Masonry coatings.
- Concrete.
- General metal coatings.

IV. SPECIFICATION

- | | |
|------------------------------------|-----------------------------------|
| • Non-Volatile (150 °C, 15 mins) | : 50 ± 1 % |
| • Viscosity (25 °C, Gardner-Holdt) | : Z ₁ - Z ₃ |
| • Acid Value (mg KOH/g solid) | : 8 - 10 |
| • Color (Gardner-Holdt) | : maximum 1 |
| • Appearance | : clean & clear |
| • Specific Gravity (25 °C) | : ca. 0.984 |

V. STANDARD PACKING

200 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.